



# BASIC ELECTRODE RANGE « Critical assemblies » SELECTARC B58





## **SELECTARC B58**

#### **TÜV Approval**

#### Electrode with thick basic coating

for high security assemblies, for a use at operational temperatures between -40°C and +400°C - Dual polarity but preferably for DC.

#### Weldable steel range:

Construction steels for general use, ship steels, steels for boiler and pressure vessels, fine grained steels, steels for tubes.

Moulded steels and for heat treatment.

Pressure vessels, piping, ship building									
Ref.	Ø (mm)	Length (mm)	Items per case	Kg per case	Case/ Package				
81403 S12	25	350	250	5	4				

81403 S12	2.5	350	250	5	4
81433 S12	3.2	350	156	5	4
81444 S12	4.0	450	97	6.5	4

More information in our technical data sheet on: http://www.fsh-welding.com/ UNIVERSAL BASIC 7018



### PRODUCT ADVANTAGES :

- Very good operator appeal
- Easy striking and re-striking
- Easy slag removal
- Excellent resilience values down to -40°C
- Great mechanical properties and high resistance to cracking

#### New packaging with ergonomic easy opening!





Find our full range of products on our literature on: www.fsh-welding.com In our range of Basic Electrodes, also look at our: Selectarc B7018S and Selectarc B7016Sp!



FSH WELDING GROUP SA 4, rue de la Fonderie 25220 Roche-les-Beaupré - France Tél : +33 3 81 60 51 72 Email : info@fsh-welding.com www.fsh-welding.com



